REVISIONES/REVISIONS				
INDICE ISSUE	DOC. APROBACION AUTHORITY DOC.	FECHA DATE	APROB APPD	VERIF SYST
-	-	XX/XX/XX	-	-

LOPA 180 PAX Y/C CONFIGURATION
A320 - MSN 1005



PART LIST				
Item	Part Number	Row	Description	Qty
1.	3510D362-31-231	1 LH	Seat Triple LH IAT	1
2.	3510D362-31-311	2-8 LH	Seat Triple LH Standard	7
3.	3510D362-31-011	9-10 & 14-29LH	Seat Triple LH Standard	18
4.	3510D362-31-031	11 LH	Seat Triple LH Standard	1
5.	3510D362-31-041	12 LH	Seat Triple LH Standard, Exit	1
6.	3510D362-31-051	13 LH	Seat Triple LH Standard, Exit	1
7.	3510D362-31-081	30 LH	Seat Triple LH Standard, Narrow, Stretcher	1
8.	3510D362-32-231	1 RH	Seat Triple RH IAT	1
9.	3510D362-32-311	2-8 RH	Seat Triple RH Standard	7
10.	3510D362-32-011	9-10 & 14-27RH	Seat Triple RH Standard	16
11.	3510D362-32-031	11 RH	Seat Triple RH Standard	1
12.	3510D362-32-041	12 RH	Seat Triple RH Standard, Exit	1
13.	3510D362-32-051	13 RH	Seat Triple RH Standard, Exit	1
14.	3510D362-32-061	28-29 RH	Seat Triple RH Standard, HC Stretcher	2
15.	3510D362-32-081	30 RH	Seat Triple RH Standard, Narrow, Stretcher	1

NOTES:

1. AISLE WIDTHS MUST MEET REQUIREMENTS SET FORTH IN EASA CS 25.815
2. EMERGENCY EXITS MUST BE ACCESSIBLE PER EASA CS 25.813
3. EMERGENCY EXIST MUST BE MARKED IN ACCORDANCE WITH EASA CS 25.811
4. ALL LIFE VESTS MUST CONFORM TO ETSO C-13
5. PASSAGEWAY TO ALL TYPE I AND TYPE III EXITS MUST NOT BE LESS THAN 20"
6. CREW OXYGEN MASKS MUST MEET ALL REQUIREMENTS IN EASA CS 25.1439
7. STORAGE PROVISIONS FOR ALL EMERGENCY EQUIPMENT MUST BE MARKED TO IDENTIFY THEIR CONTENTS IAW EASA CS 25.1561
8. ''FASTEN SEAT BELT'' AND ''NO SMOKING'' SIGNS MUST BE VISIBLE TO EACH PERSON SEATED IN THE PASSENGER CABIN
9. ALL SEAT BACKS AND BULKHEADS MUST HAVE ''FASTEN SEAT BELT WHILE SEATED'' PLACARD
10. SEAT REFERENCE LINE IS TAKEN FROM POINT OF ATTACHMENT TO AIRCRAFT SEAT TRACKS
11. LOPA FOR 180 PAX SEATS ARRANGED IAW SERVICE BULLETIN 32071-SB001. INSTALLED SEATS ARE:
    RECARO 3510D TYPE 362 SERIES iaw CMM 25-25-92
12. ALL SEATS MUST CONFORM TO RESPECTIVE TSO OR ETSO
13. TIGHTEN THE REAR TRACK FITTING FASTENER FROM 20 TO 30 lb x in (3.4 TO 4.5 N x m)
14. ENSURE THAT TRIPLE SEATS ROW 11 & 12 DO NOT RECLINE (ALL OF THEM). IF NOT, LOCK RECLINE ACCORDING TO CMM INSTRUCTIONS.
15. INSTALLATION TOLERANCES: LINEAR ± 1 mm, ANGULAR ± 0.5º
16. QUANTITY PER INSTALLATION: 1
17. (SEE POST-INSTALLATION NOTES IN THIS SHEET)

POST-INSTALLATION NOTES:

1. ENSURE EACH OXYGEN MASK DROPS WITHIN THE REQUIRED ZONE ABOVE PASSENGER SEAT
2. ENSURE NO SMOKING/FASTEN SEAT BELT SIGN IS VISIBLE TO EACH PASSENGER WHILE SEATED
3. ENSURE EMERGENCY ESCAPE PATH MARKING IS DIRECTLY VISIBLE ALONG THE WHOLE PASSENGER CABIN AND ALSO NO OBJECT OR CARPET COVERS IT AT ANY POINT OF EMERGENCY EXIT AISLES

COMPUTER PRODUCED DRAWING
NO MANUAL ALTERATION

0 10 20 30 40 50 60 70 80 90 100
MILLIMETROS
MILLIMETERS

PART LIST IN THIS SHEET

CAD CATIA	ESTE DOCUMENTO ES PROPIEDAD DE S4A TODOS LOS DERECHOS RESERVADOS / THIS DOCUMENT IS PROPERTY OF S4A WHICH RESERVES ALL RIGHTS		PROTECCION SUPERFICIAL PROTECTIVE FINISH
S4A MAINTENANCE REPAIR	RUGOSIDAD DE LA SUPERFICE Ra SURFACE ROUGHNESS Ra SEGUN PER	TOLERANCIAS NO ESPECIFICADAS LIMITS NOT STATED SEGUN PER	SEGUN PER ESPESOR DE CAPA LAYER THICKNESS COLOR COLOUR UNE Nº UNE NO
CLASE/CLASS -	MARCA DE IDENTIF IDENT MARKINGS SEGUN PER N/A	PARTE INTERCAMBIABLE INTERCHANGEABLE PART SEGUN PER F1	SI/YES NO — PARTE IDENTIFICABLE IDENTIFIABLE PART SI/YES NO — FECHA DATE MAR/18
PROYECCION PROJECTION	DIBUJ DWN S4A	COMP CHKD F. GUERRERO	RESIST STRESS F. GUERRERO
	APROB APPD A. SANCHEZ	VERIF SYST A. SANCHEZ	PESO WT Kg
ESCALA SCALE: X:X	COLECC COLLEC	DESIGNACION: TITLE: LOPA 180 PAX A320	Nº NO 32071-25200001
			HOJA SHEET 1/2 — INDICE ISSUE /